

# ABRASIVES



## CUBITRON™ II HOOKIT™ FILM DISC 775L


- To be used with random orbital sanders
- 3M® precision-shaped ceramic grain technology provides fast cut and long life
- Film backing for greater tear-resistance and edge retention
- Ideal for a wide variety of substrates and applications focused primarily on stock removal
- 3M® Hookit™ attachment makes changing discs fast and easy



Model No.	Mfg. No.	Grit	Diameter	Price /Each
NV465	AB86822	80	5"	
NV466	AB86823	120	5"	
NV467	AB64270	220	5"	
NV468	AB47081	320	5"	
NY202	AB86824	80+	6"	
NY203	AB86825	120+	6"	
NY205	AB64259	150+	6"	
NV471	AB64265	180	6"	
NY204	AB64271	220+	6"	
NY207	AB47098	240+	6"	
NY206	AB47082	320+	6"	
NY208	AB05059	400+	6"	

## CUBITRON™ II HOOKIT™ FILM DISC 775L

- To be used with random orbital sanders
- 3M® precision-shaped ceramic grain technology provides fast cut and long life
- Film backing for greater tear-resistance and edge retention
- Ideal for a wide variety of substrates and applications focused primarily on stock removal
- 3M® Hookit™ attachment makes changing discs fast and easy



Model No.	Mfg. No.	Grit	Diameter	Price /Each
NV734	AB86818	80	5"	
NV754	AB86819	120	5"	
NV748	AB64263	180	5"	
NV759	AB47080	320	5"	
NU579	AB86820	80	6"	
NU576	AB86821	120	6"	
NV703	AB87041	150	6"	
NU577	AB87040	180	6"	
NV192	AB87089	220	6"	
NV691	AB47096	240	6"	
NV193	AB47099	320	6"	
NV693	AB05056	400	6"	

## CLOTH BELT 241D

- Tube-shaped band fits inner and outer contours to remove parting lines, imperfections and burrs
- X-weight cloth backing withstands heavy sanding and grinding
- Resin bond withstands high heat and pressure
- Tough aluminum oxide abrasive mineral cuts fast and performs well on many substrates
- Abrasive Material: Aluminum Oxide



Model No.	Mfg. No.	Grit	Width	Length	Price /Each
BP033	AB66616	36	3"	24"	
BP034	AB66604	40	3"	24"	
BP035	AB66617	50	3"	24"	
BP037	AB66611	80	3"	24"	
BP031	AB66607	100	3"	24"	
BP032	AB66608	120	3"	24"	
BP043	AB66610	P60	4"	24"	
BP044	AB66611	P80	4"	24"	

## 777F CLOTH BELT

- 3M™ ceramic aluminum oxide grain blend surpasses aluminum oxide abrasives in cut-rate
- Durable ceramic/aluminum oxide blend extends belt life, producing more parts per belt and requiring fewer belt changes
- Heavyweight polyester backing supports high-pressure, tough applications and can be run wet or dry
- Contains a grinding aid to reduce heat and increase performance when used stainless steel and other exotic metals
- Long life
- Fast cutting



Model No.	Mfg. No.	Grit	Width	Length	Price /Each
NU341	AB84409	40	1/2"	18"	
NU338	AB80551	60	1/2"	18"	
NU337	AB80232	80	1/2"	18"	
NU306	AB27436	100	1/2"	18"	
NU340	AB84304	120	1/2"	18"	
NU359	AM39061	180	1/2"	18"	

## CUBITRON™ II 984F ABRASIVE BELT

- To be used with back stands, bench top motors, centreless grinders, cylindrical grinders, disc sanders, edge sanders, file belt sanders, inline sanders, manual back stands, pressure assist back stands and wide belt sanders
- 3M® precision-shaped ceramic grain continuously fractures into sharp points that cut exceptionally fast, helping increase productivity
- Engineered to run cooler, reducing metal discoloration/oxidation and the chance of heat related stress cracks
- 3M® precision-shaped ceramic grain requires less pressure, which means less operator fatigue
- YF-weight backing excels in medium to high-pressure stainless steel, cobalt chrome and nickel alloy applications
- Abrasive Material: Ceramic
- Backing Weight: YF-Weight
- Backing Material: Polyester
- Colour: Orange



Model No.	Mfg. No.	Grit	Width	Length	Price /Each
NU310	AB27511	36	1/2"	18"	
NU323	AB55041	60	1/2"	18"	
NV720	AB55064	36	3/4"	18"	
NV747	AM39679	36	1"	18"	
NU324	AB55048	80	1/2"	18"	
NV717	AB27512	36	1/2"	24"	
NV731	AB55031	60	1/2"	24"	
NV739	AB55054	80	1/2"	24"	